

ALPOE16-250

16 Port 250W PoE Switch

Features

- 16 PoE ports
- 2 Gigabit Uplink ports for high speed connection
- 2 Gigabit fiber optic ports for high speed connection
- Base on web management, easy and convenient



Specifications

Network Protocols & Standards	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3z 1000BASE-X IEEE 802.3x Flow Control IEEE 802.3af Power over Ethernet
Power Specifications	Power consumption: maximum 270W PoE Power: 250W Voltage: 100 - 240 VAC, 50 -60 Hz
Network Interface	16 - 10/100M ports (MDI / MDIX adaptive); ports with PoE features (24) 2 - 10/100/1000M Gigabit copper RJ45 ports (MDI / MDIX adaptive) 2 - SFP GBIC fiber module slots
Physical Specifications	Dimensions: 17.3" x 13.8" x 1.7"(440 x 350 x 43 mm) Weight: 12.13 lbs (5.5 kg)
Electromagnetic Radiation	CE mark, commercial FCC Part 15 Class A VCCI Class A C-Tick
Temperature	Operating: 32° - 104° F (0° - 50° C) Storage: -4° - 158° F (-20° - 70° C)
Humidity	Operating : Maximum relative humidity 90% without condensation Storage: 95% maximum relative humidity, non-condensing
Altitude	Working: Up to 10,000 feet (3,000 meters) Storage: The largest 10,000 feet (3,000 meters)
LEDs	Each device: power light Each device: WEB indicator Per port (10/100 and Gigabit): connection speed indicator Per PoE port: PoE power-on LED
Radiation / Eletromagnetic Immunity	EN 55024
Safety	CE mark, commercial, cUL 60950 (Listed) / EN60950
Performance Spec.	Forwarding modes: Store and forward Bandwidth: 12.8 Gbps (non-blocking) network latency: 100 Mbps to 100 Mbps transmission, storage and forwarding mode under a 64-byte frame delay is less than 20 microseconds Buffer memory: 3Mb per system Addressing: 48-bit MAC address the address database size: 8,000 per system MAC address Mean failure interval (MTBF): 300,000 hours (about 34 years)
Warranty	1 year