

## ALSGFMD2

### 2 Channel Fiber Optic Transmitter/Receiver

#### Features

- 8/10-bit digital code and non-compression video transmission
- Unique digital port anti-lightning design
- Automatic compatibility with PAL, NTSC and SECAM video systems
- Industry level design, surface mount technology
- Without FM, phase modulation and amplitude modulation interface
- Pure Digital and non-compressed transmission
- Status indicator light (monitors running status)
- Multimode fiber transmission only
- Advanced self-adaptive technology
- Optional web managing function
- Without EM and RF interference
- Support point to point and cascade style
- Supports customization and OEM

Note: This product is sold in pairs.



#### Specifications

<b>Video Digital-bit Wide</b>	8/10 bit
<b>Video Input / Output Impeance</b>	BNC 75Ohm non-equalilibrium interface
<b>Video Input / Output Voltage</b>	1V (1.5V Max)
<b>Signal Bandwidth</b>	> 6.5 MHz
<b>Filed Tilt Ratio</b>	< 5%
<b>Interface Type</b>	RJ-45
<b>Electrical Interface</b>	RS232 / RS422 / RS485
<b>Bit Rate</b>	RS232 - 2Kbps, RS422/485 - 25Mbps
<b>Dimensions (HxWxD)</b>	4.125" x 5.5" x 1.25"
<b>Weight</b>	Approx. 0.55 lbs
<b>Power Input</b>	AC 100~250V, 50-60Hz, AC24V, DC-48V
<b>Power Supply</b>	5V DC (included)